

Fiber Optic Wall Mount Outlet

FWT-4C

Overview

EFON FDB-004C optical distribution box terminates one fiber optic cable with up to 4 cores, bringing significant improvements resulting in better customer experience when FTTH have to be deployed.

Features

- ABS material used ensures the body strong and light.
- Easy installations: Mount on wall or just put on the ground.
- Splicing tray can be removed when needed or during the installation for the convenient operation and installation;
- Adapter slots adopted – No screws needed for installing adapters.
- Double-layer design for easier installation and maintenances:
 - ✦ Upper layer for splicing.
 - ✦ Lower layer for distribution.
- Cable fixing units(Tie-warps) provided for fixing the input optical cable.



Dimensions and Capability

Dimensions (W*H*D)	152mm x 30mm x 112mm
Adapter Capacity	4 fibers with SC / FC / LC adapters
Number of Cable Entrance/Exit	1/4
Optional Accessories	Adapters, Pigtails
Weight	0.16 KG
Max diameter of entry cable	13mm

Operation Conditions

Temperature	-5°C -- 60°C
Humidity	90% at 30°C
Air Pressure	70kPa – 106kPa

Shipping Information

Package Contents	Distribution box, 1 unit; Wall mount installation accessories, 1 set
Package Dimensions(W*H*D)	170mm*50mm*130mm
Material	Carton box
Weight	0.65 KG
Lead Time	10-15 working days normally

Part Details

